

IN THE CLAIMS

Kindly cancel claims 1-13 and insert new claims 14-25 as shown on the attached sheets.

CLAIMS - 53175

14. (new) A composition for the treatment of metal surfaces, containing

a) at least one polymer as component A, composed of the structural element

5

(1)




(1)


and at least three structural elements selected from the group consisting of

10

(2)




(3)




and/or

(4)



(5)



and/or

and/or

where

15

in structural element (1)

CLAIMS - 53175

R' is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical of less than 31 carbon atoms which may be unsubstituted or substituted by alkyl radicals or heteroatom-containing groups or may be interrupted by heteroatoms or may contain double bonds;

5 in structural element (3)

R'' and R''' are any desired radicals having a molecular weight of < 200 g/mol, in structural elements (2), (3) and (4)

M, in each case independently of one another, are hydrogen or a cation, and

10 in structural element (5)

R is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical which may be unsubstituted or substituted by alkyl radicals or heteroatom-containing groups or may be interrupted by heteroatoms;


15 b) water or another solvent which is suitable for dissolving, dispersing, suspending or emulsifying the polymer (component A), as component B;

c) if required, surface-active compounds, dispersants, suspending media and/or emulsifiers, as component C.





20 15. (new) A composition for the deposition of metals or metal alloys on plastics surfaces, containing:

a) at least one polymer as component A, composed of the structural element (1)

CLAIMS - 53175



and at least three structural elements selected from the group consisting of



where

in structural element (1)

R' is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical of less than 31 carbon atoms which may be unsubstituted or substituted by alkyl radicals or heteroatom-containing groups or may be interrupted by heteroatoms or may contain double bonds;

CLAIMS - 53175

in structural element (3)

R'' and R''' are any desired radicals having a molecular weight of < 200 g/mol,

in structural elements (2), (3) and (4)

5 M, in each case independently of one another, are hydrogen or a cation, and

in structural element (5)

R is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical which may be unsubstituted or substituted by alkyl radicals or
10 heteroatom-containing groups or may be interrupted by heteroatoms;

b) water or another solvent which is suitable for dissolving, dispersing, suspending or emulsifying the polymer (component A), as component B;

15 c) if required, surface-active compounds, dispersants, suspending media and/or emulsifiers, as component C.

16. (new) A composition as claimed in claim 14, containing, in addition to components A, B and, if required, C,

20

d) at least one salt, one acid or one base based on transition metal cations, transition metal oxo anions, fluorometallates or lanthanoids, as component D, and/or


CLAIMS - 53175

- e) at least one acid selected from the group consisting of phosphoric acid, sulfuric acid, sulfonic acids, nitric acid, hydrofluoric acid and hydrochloric acid, as component E,
- and/or
- 5 f) at least one further corrosion inhibitor as component F,
- and/or
- g) compounds of Ce, Ni, Co, V, Fe, Zn, Zr, Ca, Mn, Mo, W, Cr and/or Bi as component G,
- and/or
- 10 h) further assistants and additives as component H.

17. (new) A composition as claimed in claim 14, containing, in addition to components A, B and, if required, C:





- i) at least one metal oxide and/or metal salt as component I,
- 15 j) if required, at least one complexing agent as component J,
- k) if required, at least one acid or one alkali metal salt or alkaline earth metal salt of the corresponding acid as component K,
- l) if required, further additives as component L.

- 20 18. (new) A process for the treatment of a metal surface, wherein the metal surface is brought into contact with a polymer (component A) composed of at least one polymer as component A, composed of the structural element (1)



CLAIMS - 53175

and at least three structural elements selected from the group consisting of



where

in structural element (1)

R' is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical of less than 31 carbon atoms which may be unsubstituted or substituted by alkyl radicals or heteroatom-containing groups or may be interrupted by heteroatoms or may contain double bonds;

in structural element (3)

R'' and R''' are any desired radicals having a molecular weight of < 200 g/mol,

in structural elements (2), (3) and (4)

CLAIMS - 53175

M, in each case independently of one another, are hydrogen or a cation,

and

in structural element (5)

R is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical which

5 may be unsubstituted or substituted by alkyl radicals or heteroatom-containing groups or may be interrupted by heteroatoms.

19. (new) A process for the treatment of a metal surface, wherein the metal surface is brought into contact with a composition as claimed in claim 1.

10

20. (new) A process as claimed in claim 19, comprising the steps:

a) if required, cleaning of the metal surface for removing oils, greases and dirt,

b) if required, washing with water,

c) if required, pickling in order to remove rust or other oxides, in the presence or

15 absence of the polymer (component A) used according to the invention,

d) if required, washing with water,

e) treatment of the metal surface in the presence of the polymer (component A) used according to the invention,

f) if required, washing with water,

20 g) if required, aftertreatment, in the presence or absence of the polymer (component A) used according to the invention.


21. (new) A process for the treatment of a metal surface, wherein the metal surface is brought into contact with a composition as claimed in claim 2.

CLAIMS - 53175

22. (new) A process for the deposition of metals or metal alloys on a plastics surface, wherein the plastics surface is brought into contact with a polymer (component A) composed of





5

at least one polymer as component A, composed of the structural element (1)



and at least three structural elements selected from the group consisting of

10



15

where

CLAIMS - 53175

in structural element (1)

R' is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical of less than 31 carbon atoms which may be unsubstituted or substituted by alkyl radicals or heteroatom-containing groups or may be interrupted by heteroatoms or may contain double bonds;

in structural element (3)

R" and R''' are any desired radicals having a molecular weight of < 200 g/mol, in structural elements (2), (3) and (4)

M, in each case independently of one another, are hydrogen or a cation, and

in structural element (5)

R is hydrogen or an alkyl, cycloalkyl, aryl, aralkyl or alkaryl radical which may be unsubstituted or substituted by alkyl radicals or heteroatom-containing groups or may be interrupted by heteroatoms.

23. (new) A process for the deposition of metals or metal alloys on a plastics surface, wherein the plastics surface is brought into contact with a composition as claimed in claim 2.

24. (new) A process as claimed in claim 21, wherein a chemical or electrochemical metal deposition is carried out.

25. (new) A composition as claimed in claim 15, containing, in addition to components A, B and, if required, C,

CLAIMS - 53175

- i) at least one metal oxide and/or metal salt as component I,
- j) if required, at least one complexing agent as component J,
- k) if required, at least one acid or one alkali metal salt or alkaline earth metal salt of the corresponding acid as component K,
- 5 l) if required, further additives as component L.